


VERINS HYDRAULIQUES STANDARD
STANDARD HYDRAULIC JACKS
GATOS HIDRAULICOS ESTANDARD
HYDRAULIKZYKINDER

DIMENSIONS : mm - QUOTATION : mm
DIMENSION : mm - ABMESSUNGEN: mm



TYPE	L mini	L maxi	COURSE-STROKE CARRERA-HUB	A	B	C	N°	JOINTS-SEALS-JUNTAS-DICHTUNG				
								1	2	3	4	
20	1020	2620	1600	30	100	20	47823	43138x2	4782310	5676102x2		SE
	1120	2920	1800	30	101	20	51392	43138x2	4782310	5676102x2		SE
	1120	2920	1800	40	121	20	56399			5676107		SE
				30	60		57955			5676101x2		DE
21	920	2320	1400	50	145	35	45383	46132		5676105		SE
	1020	2620	1600	50	145	35	45384	46132		5676105		SE
	1020	2620	1600	40	125	20	46679	4667901		5676107		SE
22	400	520	120	30	60	20	53602	5360210x2	5360211	5676101x2		DE
	610	790	180	30	60	20	58778		5877911			DE
			180	30	60		57955			5676101x2		DE
	460	640	180	30	70	20	56525			5676117x2		DE
	520	760	240	30	60	20	55354	5535401		5676101x2		DE
	580	820	240	30	60	20	56921		5692111	5676101x2		DE
23	770	1140	370	30	60		52813	5281310		5676101x2		DE
24	935	2335	1400	45	89		42626		43271	5676103		SE
25	965	1465	500	30	60		48215	42881		5676101		DE

SE : simple effet - single acting - simple efecto - einfach wirkend
DE : double effet - double acting - doble efecto - doppelt wirkend

9964014A

20.09.2005

Tecnoma
technologies

S.A.S Capital 1174400 € - B.P. 195 - 51206 EPERNAY - FRANCE
Tél. 03.26.51.99.99 - Fax : 03.26.51.83.51
R.C.S. EPERNAY B 350 484 309 - APE 293D

113.25